



IMAGE FORMING APPARATUS, COMMUNICATION SYSTEM FOR MAINTENANCE
OF IMAGE FORMING APPARATUS, MAINTENANCE SERVICE METHOD OF IMAGE
FORMING APPARATUS, AND MEDIUM STORING INFORMATION TO BE USED IN
MAINTENANCE

5

BACKGROUND OF THE INVENTION

The present invention relates to an image forming apparatus
such as a copying machine or printer, a communication system for
the maintenance of an image forming apparatus, a maintenance
10 service method of an image forming apparatus, and a medium storing
information to be used in maintenance.

Network printers are in widespread use, and data is
extensively transmitted and received across networks.

Meanwhile, image forming apparatuses such as copying
15 machines and standalone type printers are not connected to
networks in almost all cases.

Even when an image forming apparatus is connected to a local
area network (to be referred to as a LAN hereinafter) and this
LAN is connected to an external network, the image forming
20 apparatus cannot be readily connected to an external system in
many instances owing to fire walls or the like. That is, presently
most image forming apparatuses cannot exchange data with external
systems via communication lines or channels.

Japanese Patent No. 2917344 proposes an invention by which
25 an image forming apparatus and an external system are connected
via a communication line, and the external system determines,
e.g., whether the apparatus can be used, by exchanging status
information of the apparatus and control signals. However, this
system is difficult to construct for the reason described above.

30

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to
provide an image forming apparatus, a communication system for
the maintenance of an image forming apparatus, a maintenance
35 service method of an image forming apparatus, and a medium storing
information to be used in maintenance, by which error information,
machine status information, operation log information, and the

like are output, as information to be used in the maintenance of an image forming apparatus, and periodically transferred to a maintenance service provider without any load on the user, thereby improving the maintenance service, e.g., predicting failures and reserving maintenance parts.

According to the present invention, there is provided an image forming apparatus for printing out data on the basis of given information, comprising a memory for storing information for use in maintenance of the image forming apparatus, a capacity determination unit for, when a use capacity of the memory has reached a predetermined value, notifying the memory of information representing that the use capacity has reached the predetermined value and instructing the memory to output the stored information, and a compressing unit for compressing the output information from the memory and outputting as coded information.

The compressing unit may also convert the output information from the memory into coded information containing a character and number or bar code type digital information, and output the converted information.

The coded information containing a character and number may be expressed by a base-10 + n (n is an integer of 1 or more) number.

A communication system for the maintenance of an image forming apparatus according to the present invention comprises the image forming apparatus having a printing unit for printing out data on the basis of given information, and a service provider's apparatus for receiving information for use in maintenance of the image forming apparatus, wherein the image forming apparatus comprises a memory for storing information for use in the maintenance of the image forming apparatus, a capacity determination unit for, when a use capacity of the memory has reached a predetermined value, notifying the memory of information representing that the use capacity has reached the predetermined value and instructing the memory to output the stored information, and a compressing unit for compressing the output information from the memory and outputting as coded

information, and the service provider's apparatus comprises information storage means for sequentially receiving and storing the coded information.

5 The printing unit of the image forming apparatus may also print the coded information output from the compressing unit, and output the printed-out sheet, and the service provider's apparatus may further comprise converting means for reading the image information printed on the printed-out sheet, converting the read image into coded information containing a character and
10 number or bar code type digital information, and outputting the converted information, an expanding unit for expanding the compressed character information or the compressed bar code type digital information, and a display unit for displaying the expanded information on a screen or printing out the expanded
15 information.

The image forming apparatus can further comprise a first facsimile unit connected to a communication line to transmit the coded information to the communication line, and the service provider's apparatus can further comprise a second facsimile unit
20 connected to the communication line to receive and output the coded information transmitted from the first facsimile unit, an expanding unit for expanding and outputting the compressed information output from the second facsimile unit, and a display unit for displaying the expanded information on a screen or
25 printing out the expanded information.

The image forming apparatus can further comprise a first server connected to a communication line to transmit the coded information to the communication line, and the service provider's apparatus can further comprise a second server connected to the
30 communication line to receive and output the coded information transmitted from the first server, an expanding unit for expanding and outputting the compressed information output from the second server, and a display unit for displaying the expanded information on a screen or printing out the expanded information.

35 The printing unit of the image forming apparatus may also print the coded information and output a first printed-out sheet, the image forming apparatus may further comprise converting means

0955374334

for reading and converting information on a second printed-out sheet into first character information, and a setting change unit for changing a set value of the image forming apparatus on the basis of the converted first character information, and the service provider's apparatus may further comprise converting means for reading and converting image information printed on the first printed-out sheet into compressed second information, and outputting the compressed second information, an expanding unit for expanding the compressed second information, a display unit for displaying the expanded second information on a screen or printing out the expanded second information, and a printing unit for outputting the second printed-out sheet containing information which designates a change of a set value of the image forming apparatus.

The image forming apparatus may further comprise a first facsimile unit connected to a communication line to transmit the coded first information to the communication line and receive second information transmitted from the communication line, and a setting change unit for changing a set value of the image forming apparatus on the basis of the received second information, and the service provider's apparatus may further comprise a second facsimile unit connected to the communication line to receive and output the coded first information transmitted from the first facsimile unit, and transmit the second information designating a change of a set value of the image forming apparatus, an expanding unit for expanding and outputting the coded compressed first information output from the second facsimile unit, and a display unit for displaying the expanded first information on a screen or printing out the expanded first information.

The image forming apparatus may further comprise a first server connected to a communication line to transmit the coded first information to the communication line, and receive the second information transmitted from the communication line, and a setting change unit for changing a set value of the image forming apparatus on the basis of the received second information, and the service provider's apparatus may further comprise a second server connected to the communication line to receive and output

5

10

20

25

35

of the image forming apparatus, on the user side, and receiving the coded information transmitted from the first facsimile unit by using a second facsimile unit connected to the communication line, expanding the compressed information received by the second
5 facsimile unit, and displaying the expanded information on a screen or printing out the expanded information, on the service provider side.

The method can further comprise the steps of transmitting the coded information to a communication line by using a first
10 server connected to the communication line, on the user side, and receiving the coded information transmitted from the first server by using a second server connected to the communication line, expanding the compressed information received by the second server, and displaying the expanded information on a screen or
15 printing out the expanded information, on the service provider side.

The method may further comprise the steps of printing the coded information and outputting a first printed-out sheet by using the printing unit, reading and converting information on
20 the first printed-out sheet into first information, and outputting the first information, and changing a set value of the image forming apparatus on the basis of the first information, on the user side, and reading image information printed on the first printed-out sheet and converting the image information into
25 compressed second information, expanding the compressed second information, displaying the expanded second information on a screen or printing out the expanded second information, and outputting a second printed-out sheet containing information which designates a change of a set value of the image forming
30 apparatus, on the service provider side.

The method may further comprise the steps of transmitting the coded first information to a communication line, and receiving second information transmitted from the communication line, by using a first facsimile unit connected to the communication line,
35 and changing a set value of the image forming apparatus on the basis of the received second information, on the user side, and receiving the coded first information transmitted from the first

09895873 15384

facsimile unit, and transmitting the second information which designates a change of a set value of the image forming apparatus, by using a second facsimile unit connected to the communication line, expanding the coded compressed first information received
 5 by the second facsimile unit, and displaying the expanded first information on a screen or printing out the expanded first information, on the service provider side.

The method can further comprise the steps of transmitting the coded first information to a communication line, and receiving
 10 second information transmitted from the communication line, by using a first server connected to the communication line, and changing a set value of the image forming apparatus on the basis of the received second information, on the user side, and receiving the coded first information transmitted from the first
 15 server, and transmitting the second information which designates a change of a set value of the image forming apparatus, by using a second server connected to the communication line, expanding the coded compressed first information received by the second server, and displaying the expanded first information on a screen
 20 or printing out the expanded first information, on the service provider side.

According to the present invention, there is provided a computer-readable storage medium storing information for use in maintenance of an image forming apparatus.

25 The information may contain information concerning an operation log of the image forming apparatus, information concerning the setting of the image forming apparatus, and information concerning a paper jamming occurrence portion.

The information may be stored as compressed coded
 30 information.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the arrangement of a user's image forming apparatus, when this user's image forming
 35 apparatus is not connected to a service provider's apparatus, according to an embodiment of the present invention;

Fig. 2 is a block diagram showing the arrangement of a

Fig. 16 is a flow chart showing the sequence of setting conditions of automatic transmission across the Internet from the user's apparatus to the service provider's apparatus;

5

10

Fig. 19 is a view for explaining an operation log as practical information to be used in maintenance; and

15

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described below with reference to the accompanying drawings.

20

35

is difficult to install expensive parts, systems, and communication equipment at the user's expense.

To transmit information by using the existing information transmission method, therefore, even when communication
5 equipment is not directly connected to an image forming apparatus, the form of output information from the image forming apparatus is once converted by some converting means, and the information is transmitted by using a general information transmission method. A service provider restores the original state of the received
10 data and uses the data in maintenance service.

As the information transmission system, a common system such as mail or a telephone line is used.

To protect maintenance information from being leaked to or altered by the third party, the maintenance information is
15 converted into coded information which is difficult or impossible to interpret by the third party. In addition, this information is a text code or a bar code made up of numbers and alphabets, so that the information is well resistant to, e.g., contamination or noise when printed on a paper surface.

The present invention includes not only a case in which the apparatus is not at all connected to any communication network, but also a case in which an image forming apparatus is connected to a LAN (Local Area Network). Even in a case like this, no mail address independent of original functions of the image forming
20 apparatus is necessary. For example, assuming this image forming apparatus is a LAN printer, information can be transferred to a service provider as long as an IP address required for normal operations as a printer is available.

Also, data such as machine status information and use log
30 information is stored in an image forming apparatus, but these pieces of information require a large capacity. However, a large-capacity memory is expensive.

Accordingly, an inexpensive small-capacity memory is used. When the information storage amount reaches, e.g., 90% of the
35 memory capacity, information is output outside the apparatus to reset the memory, and new information is written, thereby preventing capacity insufficiency of the memory.

202507 225555

Furthermore, when analyzing supplied information and detecting the state of a user's image forming apparatus, a service provider sometimes determines that various set values should be changed. In this case, the service provider sends to the user

5 information concerning changes of set values by mailing a printed sheet of paper, by FAX transmission, or by electronic data transmission across a network. The user converts the image information sent by mail or FAX transmission into character information by OCR conversion using a scanner, and loads this

10 character information into the image forming apparatus. Alternatively, the user receives the electronic data by a computer connected to the network and inputs the received data to the image forming apparatus. This information contains data serving as a trigger for permitting the image forming apparatus to

15 automatically activate a setting change sequence. This data automatically activates the setting change sequence to change various set values in the image forming apparatus.

The output information from the user's image forming apparatus desirably contains the following:

- 20 (a) Coded data to be used in maintenance
- (b) Document I (which informs a user that data (a) represents an operation log and the like and is effective in maintenance service, so it is recommended to save this data without discarding it)
- 25 (c) Document II (which informs a user that transmitting to the FAX number or mailing to the mail address of the service provider mentioned (the receiving side is charged in either case) is useful for predictive maintenance, and the service improves)

When reading these documents I and II, the user is highly

30 likely to send by FAX transmission or mail a printed-out sheet on which the coded data is printed, or at least save the data without discarding it.

In particular, when the image forming apparatus does not properly operate, the user voluntarily sends the printed-out

35 sheet by FAX transmission or mail at high possibility.

Note that even if the user loses the coded information for maintenance, the maintenance service can be performed. However,

0989557 1334

more appropriate steps can be taken with the information.

The form of the coded data will be described below.

Pieces of information for use in maintenance, e.g., status information, setting information, operation log information, and error log information of an image forming apparatus are expressed by decimal numbers with breaks. These decimal numbers are converted into base-32 numbers which represent data by combining numbers 0 to 9 and alphabets A to V, and a predetermined mark is inserted in each break (e.g., "#" is inserted to represent a delimiter between information contents, and "+" is inserted to represent a delimiter between sequences or items). By the use of this method, maintenance information which is often long can be shortened.

The information can be further shortened by using base-64 numbers by combining 0 to 9, A to Z, a to z, and symbols such as \$ and %.

Furthermore, the information can also be expressed by the realization of base-128 numbers by adding 52 half-sized katakana characters and various symbols such as "-", "*", "/", ¥, and "@". This can further shorten the information.

Note that base-16, base-32, base-64, and base-128 numbers are used as examples, but the present invention is not limited to these methods. For example, any method such as base-50 or base-100 numbers capable of compressing information by using numbers, characters, and symbols can be applied to coding of the present invention.

Also, the information coded as described above can also be expressed as follows as bar code type digital data other than characters and numbers.

30 |■■■■■|■■■|■■■|■■■■■|■|■||■■■|
 ■■■|||■■■■■|■■|■■■■■|■■|■■■|■|■

When the image information is constructed as this bar code type digital data, no OCR means for reading this image information is necessary, unlike in the case of character information. Since this simplifies the arrangement of the entire apparatus, the cost can be reduced. However, the code description length often increases. Accordingly, it is desirable to summarize and arrange

5

10

20

25

30

35

is received and stored in a database at appropriate timings. If the service provider has no such apparatus, the received information is printed out and stored in the conventional manner.

Also, a user's image forming apparatus is in some instances
5 connected to an external system across a LAN. In this case, the coded information is converted into a predetermined file format or packet format and automatically transferred periodically to a service station's computer address by using ftp (file-transport-protocol) or the like, without any user's operations.

10 If data transfer fails, the operation is switched to a method for a standalone type image forming apparatus, and the coded information and documents I and II are printed out. The user is prompted to send the printed data to the service provider by mail or by manual FAX transmission.

15 The arrangements of a user's image forming apparatus and a service provider's apparatus for receiving information, when the user's image forming apparatus and a service provider's computer or the like are not connected by a network or the like, will be described below with reference to the accompanying
20 drawings.

Fig. 1 shows the arrangement of the user's image forming apparatus. This image forming apparatus includes a copying machine, printer, or the like.

A central processing unit (to be referred to as a CPU
25 hereinafter) 1 controls printing operation and the like of the whole apparatus. In this embodiment, the CPU 1 transfers information 11 for use in maintenance to a memory 2. This information 11 includes, e.g., apparatus setting information, status information (status log), error information concerning
30 a paper jamming occurrence portion or the like, an operation log, a part exchange warning, and necessary maintenance messages.

The memory 2 is a rewritable memory such as a RAM (Random Access Memory) and is preferably a detachable storage. This memory 2 stores the information 11 given by the CPU 1.

35 A capacity determination unit 3 detects the use ratio of the memory 2. If stored information reaches a predetermined ratio (e.g., 90%) of the capacity allocated to storage, the

capacity determination unit 3 notifies the memory 2 of this information and instructs the memory 2 to output the stored information.

When thus instructed to output the stored information by the capacity determination unit 3, or when the user instructs the memory 2 to output the stored information by selecting an operation menu of the apparatus, the memory 2 outputs and transfers stored information 12 to a compressing unit 4.

The compressing unit 4 compresses the output information 12 from the memory 2 into coded information 13 by using, e.g., base-32 notation (to be described later), and outputs this coded information 13 to a printing unit 5.

This printing unit 5 has a printing function normally installed in an image forming apparatus. The printing unit 5 prints out the coded information 13 onto a sheet of paper.

The information printed on the paper surface is a list of at least the apparatus identification number, error information, operation log information, and apparatus status information, in the form of a text code including numbers or alphabets. This information can also be bar code type digital data.

Since the compressing unit 4 compresses the information, it is possible to reduce the number of printing sheets and the cost. Also, since the printed contents are coded, the contents are not interpreted by the third party. This can prevent a leakage of secrets.

Fig. 2 shows the arrangement of the apparatus of the service provider which has received a printed sheet 20. The image information printed on the sheet 20 is given as it is sent by mail from the user to the service provider or transmitted by FAX transmission to the receiving (printing) apparatus of the service provider.

An OCR unit 21 reads this image information printed on the sheet 20 and outputs it as character information 31.

This character information 31 is compressed as described above. An expanding unit 22 expands this compressed information to restore uncompressed information 32, thereby obtaining electronic data (file).

In step S14, input of a machine number code is displayed as a setting content to be selected on the screen of the apparatus. Similarly, input of a service provider IP address setting code is displayed in step S18, and input of a service provider FAX number setting code is displayed in step S22. The user is prompted to select one of them.

When the key input sequence is selected, the processing

In step S92, the machine number of the apparatus is stored

The procedures of sequentially selecting and inputting the machine number, center computer IP address, and FAX number have been explained. However, it is also possible to set a setting mode by which these pieces of information are simultaneously read and input by the scanner.

(4) Sequence of outputting apparatus information etc.

As shown in Fig. 7, in step S100 printing of apparatus information and the like is waited for.

In step S102, a new job is input.

In step S106, the contents of the job are checked.

In step S108, operation log information is checked. This operation log information contains a printing mode selected from, e.g., forced black-and-white, color, and automatic selection, the number of copies, the type of selected sheet, a size change ratio, one-sided or two-sided, and the like.

In step S110, the operation log information is saved in the memory. As described earlier, this memory is desirably a detachable memory, e.g., a card type memory, so as to facilitate maintenance.

In step S112, the job is activated. In step S114, the flow advances to a printing sequence.

In step S116, the job is terminated. This termination includes forced termination caused by an error such as paper jamming.

In step S118, work log data is formed. This work log data contains, e.g., the number of copies, black-and-white or color,

and size. If there are an error produced by the printing process and a warning message, these pieces of information are also contained.

In step S120, the work log is saved in the memory.

5 In step S122, the use capacity of the memory is checked. If the use capacity is 90% or less, the flow advances to step S124, and the flow returns to the waiting state in step S100. If the use capacity exceeds 90%, the flow advances to a sequence of outputting the work log in step S126.

10 (5) Sequence of manually printing out data

As shown in Fig. 8, in step S130 a printing waiting state is set.

In step S132, the user operates the control panel to select data output in accordance with the display on the screen of the
15 apparatus.

In step S134, the flow advances to a sequence of outputting data to the outside.

(6) Sequence of automatically outputting data

When the image forming apparatus has a function of
20 automatically outputting data, the following sequence is executed.

As shown in Fig. 9, in step S140 an external data output sequence is waited for.

In step S142, the flow advances to a sequence of checking
25 the output format. The contents of this sequence will be explained in (7) work log external output format check sequence to be described below.

After the output format is checked, data is read out from the memory and automatically transmitted in the designated
30 external output format by facsimile or across a network in step S144.

In step S146, whether the transmission is successful is checked. If the transmission is unsuccessful, in step S148 the number of times of the output is checked. If the output is the
35 first time, the flow returns to step S144 to again output the data. If the output is the second time, the process is aborted in step S152. If the output is successful, the memory is reset

in step S150.

(7) Sequence of checking external data output format

To check the external output format of data in step S142 described above, the following sequence processing is performed.

5 As shown in Fig. 10, in step S160 a sequence of checking the external output format of data is waited for.

In step S162, whether the apparatus is connected to a LAN is checked. If the apparatus is connected, whether the apparatus is connected to a center computer of the LAN is checked in step 10 S164. If the apparatus is connected, it is determined in step S166 that data is to be output across the LAN. If the apparatus is not connected to a LAN, or if the apparatus is connected to a LAN but is not connected to a service provider's center computer, the flow advances to step S168.

15 In step S168, whether the apparatus is connected to a telephone line is checked. If the apparatus is connected, data is transmitted to a service provider's facsimile apparatus by automatic FAX transmission in step S170. If the apparatus is not connected to a telephone line, data such as operation log 20 information is converted into coded text information or bar code type digital information and printed out in step S172.

(8) Sequence by which image forming apparatus prints out data by itself

When the image forming apparatus is to print out data by 25 itself by using a built-in printing function, the following procedure is performed.

In step S180, a sequence of printing out work log information is waited for.

In step S182, a printing operation is checked to check 30 whether there is a job waiting for printing. If a waiting job is present, the job is printed in step S184.

If there is no waiting job, data is read out from the memory and printed out in the designated external output format in step S186.

35 (9) Information transfer forms between user and service provider

The following five types of forms are possible as a method

09395537 1033001

If, as a result of the deduction of the maintenance contents, the set conditions of the apparatus are to be changed in step S236, the contents are converted into the coded data 222 and printed out in step S226. The output coded data is printed out by the user via the FAX terminal 220, the telephone line 201, and the FAX terminal 200, or mailed to the user in step S219.

First, in step S206, the coded data on the printed sheet
15 is loaded by a scanner. In step S210, the loaded data is converted
into electronic image data by using an OCR means, obtaining coded
data 212 concerning information of the set conditions. In step
S214, whether a code for changing the setting of the conditions
is present is checked. If this code is present, the contents of
20 the memory are rewritten in step S218. If no such code is present,
the processing is aborted in step S216.

25 (9-4-1) Setting of FAX number for automatic FAX
transmission

In step S250, the execution of an apparatus condition setting sequence is started.

35 Henceforth, two processes must be performed. First, in
step S254, the user selects a code for setting a function of
performing automatic FAX transmission from a menu on the screen

of the apparatus.

In step S256, an automatic FAX transmission ON/OFF select menu is displayed on the screen. In step S258, the user selects ON. In step S260, the flow returns to the apparatus condition
5 setting sequence standby mode.

Next, in step S262, the user selects a window for setting the FAX number for automatic FAX transmission.

In step S264, the window for inputting the service provider's FAX number is displayed. In step S266, the FAX number
10 is input and set. After that, the flow returns to the standby mode in step S260.

(9-4-2) Automatic FAX transmission

By using the set FAX number, the built-in FAX unit of the user's image forming apparatus automatically transmits
15 information such as the apparatus status to the service provider's FAX terminal by facsimile. If transmission is impossible owing to, e.g., an operation error of the FAX terminal, the information is printed out as usual and transmitted by facsimile by using a FAX terminal different from the image forming apparatus.

As shown in Fig. 14, whether the automatic FAX transmission function is ON or OFF is checked in step S270.

If this function is OFF, the information is printed out as usual and mailed or manually transmitted by facsimile in step S272. If this function is ON, an automatic FAX transmission
25 sequence is started from step S276.

In step S276, the connection of the FAX line is checked. If the line is not connected, the information is printed out as usual and mailed or manually transmitted by facsimile in step S278. If the line is connected, automatic FAX transmission is
30 executed in step S280.

When the information is automatically transmitted from the user's image forming apparatus to the service provider's FAX terminal by facsimile, this information is directly stored in the memory in the form of electronic data if the service provider's
35 FAX terminal has a function of storing the information. If no such function is available, the information is printed out as in common FAX reception.

09557-4004

(9-5) User's image forming apparatus connected to service provider's computer via LAN, telephone line, or the like

Fig. 15 shows an arrangement in which a plurality of user's image forming apparatuses are connected to a service provider's computer across, e.g., the Internet.

A plurality of users have, as image forming apparatuses, copying machines 332, 335, and 338 and printers 333, 336, and 339 connected to personal computers 331, 334, and 337, respectively. These apparatuses are connected to the Internet 300 via user servers 320, 322, and 324, a telephone line 310, a radio communication channel 312, and an optical communication line 314. A service provider's station server 302 is connected to the Internet 300. This station server 302 is connected to a dedicated database 304 for storing information necessary for maintenance, such as apparatus status information.

With this system configuration, file type or packet type electronic data containing coded data of, e.g., apparatus status information can be automatically transmitted from the user server to the IP address of the station server by using a data transfer means such as ftp. This improves the transfer efficiency.

Practical process procedures of this data transfer will be explained below with reference to the accompanying drawings.

(9-5-1) Setting of automatic transmission destination address

To automatically transmit the apparatus status information and the like across the Internet from the user server to the station server, the address of the transmission destination must be set on the user side.

As shown in Fig. 16, the flow enters the execution of an apparatus condition setting sequence in step S350.

In step S352, the flow enters an apparatus condition setting sequence standby mode.

In step S354, the user selects a code number for setting a function of automatically transmitting the apparatus information across the Internet.

In step S356, a window for selecting ON or OFF of this automatic transmission is displayed. In step S358, the user

5 If the user server is connected to a LAN, automatic
transmission is executed across the Internet in step S386.

Automatic transmission from the user server to the service station server is executed by the following practical operation procedure.

In step S390, ftp execution batch processing is activated. In step S392, an ftp destination address is set, a transmission destination, i.e., a folder of a data storage destination is set, and data to be transmitted is set.

(10) Data processing by service provider

If the received data is the printout from the FAX terminal or image information formed on the printed-out sheet sent by mail, the service provider returns the data to electronic text code data by using a bar code reader when the data is bar code information or by using an OCR means when the data is a character code. If the data sent from the user is electronic data by automatic FAX transmission or transmission across the Internet, an electronic text data portion contained in this data is extracted.

Operation recording period

Operation log information (e.g., color or black-and-white,

mail, facsimile, and mail of a printed-out sheet. In accordance with an attached explanation/request document addressed to the user, the user sets the sent image data on a scanner, reads change information by the scanner, and inputs the information to the
5 image forming apparatus. Data written at the beginning of the input coded data triggers a set value writing sequence previously input to the image forming apparatus, thereby automatically starting a set value writing process. This sequence is substantially analogous to that described in item (3) above and
10 shown in Fig. 6.

In this sequence, copy and set value writing processes and the like are displayed by, e.g., code numbers or icons in a selection menu on the control panel. When the user selects a set value writing process, the set value is rewritten by a value
15 indicated by the supplied code information.

The above embodiments are merely examples. Therefore, these embodiments do not restrict the present invention and can be variously modified where necessary. For instance, operation log information, error information, apparatus status information, and the like are described as examples of information of the image
20 forming apparatus. However, any information useful to improve the maintenance service can be applied to the present invention and sent to the service provider.